


## FHT-TL-139



### Specification

Power Supply : 100V ~ 240V AC  
Control Circuit : 24V DC  
Power Consumption : 30W  
Operating Temper range : -25°C ~ +70°C  
Protection level (IP) :  $\geq 44$   
Humidity : 95%  
MCBF : 5 Million Cycles  
Hydraulic damper : Adjustable  
Solenoid : 24V DC 100%  
Throughout : Person  
Communication Interface : RS485 or TCP IP  
passage width :  $\leq 650$ mm  
Frequency :  $< 50$ Hz or 60Hz  
Electro -magnetic drive : DC  
Section Version : 120 degree  
No of arms : 3 arms  
Dimensions : 1630 x 1500 x 2310mm  
Net weight : 220kg

### Feature:

- ▶ Designed for secure operation with aesthetics in mind
- ▶ Corrosion protected S/S frame
- ▶ Minimal exposed hardware
- ▶ Heavy Gauge materials ASTM Standard
- ▶ Consists of rotor assembly, shield
- ▶ Assembly, barrier section, mechanism housing & ceiling plate  
The barrier can be set to delay closing in 1 ~ 60s after a
- ▶ valid card reading
- ▶ Single passage in the set direction  
Bi-directional single passage  
Free passage in the direction  
Always free or locked